

# EN - CB PNI ML90 ANTENNA WITHOUT CABLE

## Installation instructions:

- Connect the antenna to the magnetic base (not included) then fix it to the car, preferably in the middle of the car dome.
- Connect the antenna to a CB radio and test the S.W.R. in an open area.
- If it is necessary to tune the antenna, we recommend performing it only by specialized personnel with dedicated equipment.
- Connect the PL259 connector on the end of the magnet cable to the antenna connector on the back of the CB radio.

Note: PNI antennas come tuned from the factory.

## Technical specifications:

Frequency	26 – 30 MHz
S.W.R.	$\leq 1.2:1$
Impedance	50 Ohm
Maximum supported power	150 W continuously
Height	71 cm
Whip material	Fiber glass

# RO - ANTENA CB PNI ML90 FARA CABLU

## Instalare:

- Conectati antena la o baza magnetica (nu este inclusa) apoi fixati-o pe autoturism, de preferinta pe mijlocul cupolei masinii.
- Conectati antena la o statie radio CB si testati S.W.R.-ul intr-o zona deschisa cu ajutorul unui reflectometru.
- Daca este necesara calibrarea antenei, recomandam efectuarea ei doar de personal specializat cu aparatura dedicata.
- Conectati mufa PL259 din capatul cablului magnetului la mufa de antena din spatele statiei.

Nota: Antenele PNI vin calibrate din fabrica.

## Caracteristici tehnice:

Frecventa	26 – 30 MHz
S.W.R.	$\leq 1.2:1$
Impedanta	50 Ohm
Putere max. suportata	150 W continuu
Inaltime	71 cm
Material spic	Fibra de sticla